RCW 46.44.041 Maximum gross weights—Wheelbase and axle factors. No vehicle or combination of vehicles shall operate upon the public highways of this state with a gross load on any single axle in excess of twenty thousand pounds, or upon any group of axles in excess of that set forth in the following table, except that two consecutive sets of tandem axles may carry a gross load of thirty-four thousand pounds each, if the overall distance between the first and last axles of such consecutive sets of tandem axles is thirty-six feet or more.

The following table is based on the following formula: W = 500((LN/N-1)+12N+36). W is the maximum weight in pounds (to the nearest 500 pounds) carried on any group of two (2) or more consecutive axles. L is the distance in feet between the extremes of any group of two (2) or more consecutive axles. N is the number of axles under consideration.

Distance in feet between the extremes of any	Maximum load in pounds carried on any group of 2 or more consecutive axles					
group of 2 or more	2 3 axles axles	4 5 axles axle	s axles	7 axles	8 axles	9 axles
consecutive	aries aries	aries arie	s aries	aries	axies	aries
axles	24.000					
4 5	34,000 34,000					
6	34,000					
7	34,000					
8 & less	34,000 34,00					
more than 8 9	38,000 42,00 39,000 42,50					
10	40,000 43,50					
11	44,00					
12 13	45,00 45,50					
14	46,50		00			
15	47,00					
16 17	48,00 48,50					
18	49,50					
19	50,00	0 54,500 60,0	00 65,000			
20 21	51,00 51,50		00 66,000 00 66,500	72,000		
21 22	52,50	0 56,500 61,5		72,500		
23	53,00	0 57,500 62,5	00 68,000	73,000		
24	54,00			74,000	80.000	
25 26	54,50 55,50	0 58,500 63,5 0 59,500 64,0	00 69,000 00 69,500	74,500 75,000	$80,000 \\ 80,500$	
27	56,00	0 60,000 65,0	00 70,000	75,500	81,000	
28 29	57,00		00 71,000	76,500 77,000	82,000 82,500	87,500 88,000
29 30	57,50 58,50	0 61,500 66,0 0 62,000 66,5	00 71,500 00 72,000	77,500	82,500 83,000	88,000 88,500
31	59,00		00 72,500	78 000		89,000
32	60,00	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	00 72,500 00 73,000	78,500	83,500 84,500	90,000
33 34		64,000 68,5 64,500 69,0	00 74,000 00 74,500	79,000 80,000	85,000	90,500
35		65,500 70,0		80,500	$85,500 \\ 86,000$	91,000 91,500
36		66,000 70,5	00 75,500	81,000	86,500	92,000
37 38		66,500 71,0 67,500 71,5	00 76,000	81,500	87,000 87,500	93,000 93,500
39		68.000 72.5	00 77,000 00 77,500	82,000 82,500	88,500	93,300 94,000
40		68,500 73,0	00 78,000	83,500	89,000	94,500
41 42		69,500 73,5 70,000 74,0	00 78,500 00 79,000	84,000 84,500	89,500 90,000	95,000
42		70,500 75,0		85,000	90,000	95,500 96,000
44		/1,500 /5,5	00 80,500	85,500	91,000	96,500
45 46		72,000 76,0		86,000	91,500	97,500
40		72,500 76,5 73,500 77,5		87,000 87,500	92,500 93,000	98,000 98,500
48		74,000 78,0	00 83,000	88,000	93,500	99,000
49 50		74,500 78,5 75,500 79,0		88,500 89,000	94,000 94,500	99,500 100,000
51		76,000 80,0		89,500	95,000	100,000
52		76,500 80,5		90,500	95,500	101,000
53 54		77,500 81,0 78,000 81,5		91,000 91,500	96,500 97,000	102,000 102,500
55		78,500 82,5		92,000	97,500	102,500
56		79,500 83,0	00 87,500	92,500	98,000	103,500
57 58		80,000 83,5	00 88,000	93,000 94,000	98,500 99,000	104,000
58 59		84,0 85,0		94,000 94,500	99,000 99,500	$104,500 \\ 105,500$
60		85,5	00 90,000	95,000	100,500	105,500
61		86,0 86 5		95,500	101,000	$105,500 \\ 105,500$
62 63		86,5 87,5			101,500 102,000	105,500
64		88,0	00 92,500	97,500	102,500	105,500
65		88,5		98,000	103,000	105,500
66 67		89,0 90,0			103,500 104,500	$105,500 \\ 105,500$
07		90,0		,000	101,000	100,000

Distance in feet between the extremes of any	on any group of 2 or more consecutive axles								
group of 2 or	2	3	4	5	6	7	8	9	
more	axles	axles	axles	axles	axles	axles	axles	axles	
consecutive									
axles									
68				90,500	95,000	99,500	105,000	105,500	
69				91,000	95,500	100,000	105,500	105,500	
70				91,500	96,000	101,000	105,500	105,500	
71				92,500	96,500	101,500	105,500	105,500	
72				93,000	97,000	102,000	105,500	105,500	
73				93,500	98,000	102,500	105,500	105,500	
74				94,000	98,500	103,000	105,500	105,500	
75				95,000	99,000	103,500	105,500	105,500	
76				95,500	99,500	104,500	105,500	105,500	
77				96,000		105,000	105,500	105,500	
78				96,500	101.000	105,500	105,500	105,500	
79				97,500	101.500	105,500	105,500	105,500	
80				98,000	102.000	105,500	105,500	105,500	
81				98,500		105,500		105,500	
82				99,000			105,500	105,500	
83				100,000			105,500	105,500	
84						105,500		105,500	
85							105,500	105,500	
86 or more						105,500		105,500	
					,	,000		,000	

When inches are involved: Under six inches take lower, six inches or over take higher. The maximum load on any axle in any group of axles shall not exceed the single axle or tandem axle allowance as set forth in the table above.

The maximum axle and gross weights specified in this section are subject to the braking requirements set up for the service brakes upon any motor vehicle or combination of vehicles as provided by law.

Loads of not more than eighty thousand pounds which may be legally hauled in the state bordering this state which also has a sales tax, are legal in this state when moving to a port district within four miles of the bordering state except on the interstate system. This provision does not allow the operation of a vehicle combination consisting of a truck tractor and three trailers.

Notwithstanding anything contained herein, a vehicle or combination of vehicles in operation on January 4, 1975, may operate upon the public highways of this state, including the interstate system within the meaning of section 127 of Title 23, United States Code, with an overall gross weight upon a group of two consecutive sets of dual axles which was lawful in this state under the laws, regulations, and procedures in effect in this state on January 4, 1975. [2016 c 24 s 1; 1997 c 198 s 1; 1995 c 171 s 1. Prior: 1993 c 246 s 1; 1993 c 102 s 3; prior: 1988 c 229 s 1; 1988 c 6 s 2; 1985 c 351 s 3; 1977 c 81 s 2; 1975-'76 2nd ex.s. c 64 s 22.]

Effective date of 1993 c 102 and c 123-1993 sp.s. c 23: See note following RCW 46.16A.455.

Effective dates—Severability—1975-'76 2nd ex.s. c 64: See notes following RCW 46.16A.455.